



BTA/BTB20 Series
20A TRIACs
3 Quadrants
4 Quadrants




ShenZhenHanKingyuan
Electronic CO.,Ltd




TO-220A Insulated




TO-220B Non-Insulated



TO-220F Insulated



TO-263



FEATURES

> IT(RMS): 20A > VGT: $\leq 1.5V$ > VDRM VRRM:800V~1200V

APPLICATIONS

Washing machine,vacuums, massager,solid state relay, AC Motor speed regulation and so on.

Absolute Maximum Ratings (T_J=25°C unless otherwise specified)

| Symbol | Parameter | Conditions | Ratings | Unit |
|------------------|-----------------------------------|---|----------|------------------|
| VDRM | Repetitive Peak Off-State Voltage | BTA24-800 | 800 | V |
| VRRM | | BTA24-1000 | 1200 | V |
| IT(RMS) | R.M.S On-State Current | T _c =110°C | 25 | A |
| ITSM | Surge On-State Current | t _p =16.7ms/t _p =10ms | 280/300 | A |
| I ² t | I ² t for fusing | T _p =10ms | 520 | A ² s |
| PG(AV) | Average Gate Power Dissipation | T _j =125°C | 1 | W |
| IGM | Peak Gate Current | T _j =125°C | 6 | A |
| T _j | Operating Junction Temperature | | ~ 40~125 | °C |
| TSTG | Storage Temperature | | ~ 40~150 | °C |

Electrical Characteristics (T_J=25°C unless otherwise specified)

| Symbol | Parameter | Test Conditions | Value | | | | Unit |
|--------|---|---|-------|-----|-----|------|------|
| | | | SW | CW | BW | B | |
| IDRM | Repetitive Peak Off-State Current | T _j =25°C | 5 | | | | uA |
| | | T _j =125°C | 3 | | | | mA |
| IRRM | Repetitive Peak Reverse Current | T _j =25°C | 5 | | | | uA |
| | | T _j =125°C | 3 | | | | mA |
| VTM | Forward "on" voltage | IT=35A t _p =380us | 1.55 | | | | V |
| VGT | Gate trigger voltage | VD=12V ,RL=30Ω | ≤1.5 | | | | V |
| di/dt | Critical rate of rise of on-state current | I,II,III F=120Hz,T _j =125°C IG=2xIGT ,tr≤100ns | ≥50 | | | | A/us |
| | | | IV | ≥10 | | | |
| IGT | Gate trigger current | I,II,III VD=12V RL=30Ω | ≤10 | ≤35 | ≤50 | ≤50 | mA |
| | | | | / | / | ≤100 | mA |
| IH | Holding current | IT=0.2A | ≤40 | ≤60 | ≤80 | ≤80 | mA |
| VDG | Gate non-trigger voltage | ALL VD=VDRM T _J =125°C | ≥0.2 | | | | V |

FIG1

Maximum power dissipation versus RMS on-state current




FIG2

RMS on-state current versus case temperature




FIG3

Surge peak on-state current versus number of cycles




FIG4

On-state characteristics (maximum values)




FIG5

Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 20ms$, and corresponding value of I^2t ($di/dt < 100A/\mu s$)






FIG6

Relative variations of gate trigger current, holding current and latching current versus junction temperature




PACKAGE MECHANICAL DATA



TO-220A Ins


| Ref. | Dimensions | | | | | |
|------|-------------|------|------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 4.40 | | 4.60 | 0.173 | | 0.181 |
| B | 0.61 | | 0.88 | 0.024 | | 0.035 |
| C | 0.46 | | 0.70 | 0.018 | | 0.028 |
| C2 | 1.21 | | 1.32 | 0.048 | | 0.052 |
| C3 | 2.40 | | 2.72 | 0.094 | | 0.107 |
| D | 8.60 | | 9.70 | 0.339 | | 0.382 |
| E | 9.80 | | 10.4 | 0.386 | | 0.409 |
| F | 6.55 | | 6.95 | 0.258 | | 0.274 |
| G | | 2.54 | | | 0.1 | |
| H | 28.0 | | 29.8 | 1.102 | | 1.173 |
| L1 | | 3.75 | | | 0.148 | |
| L2 | 1.14 | | 1.70 | 0.045 | | 0.067 |
| L3 | 2.65 | | 2.95 | 0.104 | | 0.116 |
| V1 | | 45° | | | 45° | |

| Ref. | Dimensions | | | | | |
|------|-------------|------|------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 4.40 | | 4.60 | 0.173 | | 0.181 |
| B | 0.61 | | 0.88 | 0.024 | | 0.035 |
| C | 0.46 | | 0.70 | 0.018 | | 0.028 |
| C2 | 1.21 | | 1.32 | 0.048 | | 0.052 |
| C3 | 2.40 | | 2.72 | 0.094 | | 0.107 |
| D | 8.60 | | 9.70 | 0.339 | | 0.382 |
| E | 9.60 | | 10.4 | 0.378 | | 0.409 |
| F | 6.20 | | 6.60 | 0.244 | | 0.260 |
| G | | 2.54 | | | 0.1 | |
| H | 28.0 | | 29.8 | 1.102 | | 1.173 |
| L1 | | 3.75 | | | 0.148 | |
| L2 | 1.14 | | 1.70 | 0.045 | | 0.067 |
| L3 | 2.65 | | 2.95 | 0.104 | | 0.116 |
| V1 | | 45° | | | 45° | |



TO-220B Non-Ins


PACKAGE MECHANICAL DATA



TO-220F Ins

| Ref. | Dimensions | | | | | |
|------|-------------|------|------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 4.50 | | 4.90 | 0.177 | | 0.193 |
| B | 0.74 | 0.80 | 0.83 | 0.029 | 0.031 | 0.033 |
| C | 0.47 | | 0.65 | 0.019 | | 0.026 |
| C2 | 2.45 | | 2.75 | 0.096 | | 0.108 |
| C3 | 2.60 | | 3.00 | 0.102 | | 0.118 |
| D | 8.80 | | 9.30 | 0.346 | | 0.366 |
| E | 9.80 | | 10.4 | 0.386 | | 0.410 |
| F | 6.40 | | 6.80 | 0.252 | | 0.268 |
| G | | 2.54 | | | 0.1 | |
| H | 28.0 | | 29.8 | 1.102 | | 1.173 |
| L1 | | 3.63 | | | 0.143 | |
| L2 | 1.14 | | 1.70 | 0.045 | | 0.067 |
| L3 | | 3.30 | | | 0.130 | |
| V1 | | 45° | | | 45° | |

| Ref. | Dimensions | | | | | |
|------|-------------|------|-------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 9.90 | | 10.20 | 0.390 | | 0.402 |
| B | 14.70 | | 15.80 | 0.579 | | 0.622 |
| C | 9.4 | | 9.6 | 0.37 | | 0.378 |
| D | | 2.54 | | | 0.100 | |
| E | 1.20 | | 1.40 | 0.047 | | 0.055 |
| F | 0.75 | | 0.85 | 0.029 | | 0.033 |
| G | | | 1.75 | | | 0.069 |
| H | 4.40 | | 4.70 | 0.173 | | 0.185 |
| J | 2.30 | | 2.70 | 0.091 | | 0.106 |
| K | 0.38 | | 0.55 | 0.015 | | 0.022 |
| L | 0 | 0.10 | 0.25 | 0 | 0.004 | 0.010 |
| M | 1.25 | | 1.35 | 0.049 | | 0.053 |



TO-263



ShenZhenHanKingyuan
Electronic CO.,Ltd

Information furnished is believed to be accurate and reliable. However, Shenzhen HanKingyuan Electronic assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied.

The KY logo is a registered trademark of Shenzhen HanKingyuan Electronic.

©2013 Shenzhen HanKingyuan Electronic - Printed in Shenzhen - All Rights Reserved